

Grain Bagger

AKRON® TAKE THE ADVANTAGE AT YOUR FIELD

- Thick heavily reinforced horizontal auger.
- Heavy-duty frame built with shaped tubes and stamped sheets.
- · High capacity reception hopper.
- Transmission through a chain and heat-treated gears. Self-adjusting chain tensioner.
- User-friendly mechanical height adjustment.
- Power Required: 60 HP
- Rubber Flap that prevents grain spillage.
- "EASY LIFT" Cradle System that notably makes it easier to install the grain bag. It minimizes the required number of operators.
- Hydraulic Brake. Easy to adjust. Precise system.
- Wheel configuration that allows either to operate or transport the machine without any wheel position change.
- Tires: 7.50 X 16
- Electrostatic polyurethane paint.



Great Capacity!!! 400 ton/hour

Easy transport without the need to change wheel position.

Tunnel for bags of 9 feet Steady flow bagging 400 ton/hr - 14700 bu/hr performance **Power Required** 60 HP Tube/ Auger Diameter 410 mm / 16 9/64 in **Hopper Capacity** 1850 L / 488 gals

AKRON may change specifications and product designs in this or other brochures at any time, without previous notice. Images for illustrative purposes only.











Rosario de Santa Fe 2256 X2400EFN San Francisco CBA, Argentina E-mail: export@akron.com.ar www.akron.com.ar Tel: +54 3564 498502 Fax: +54 3564 436777 ext 110

